

Datacom Technology Ltd

RF- Serial 5000.1 Point To Point Low Power Radio System

Features:

- Master unit – RS232 input/output.
- Slave unit – RS232 input/output.
- Full 2 way half duplex communication between master & multi slave units.
- Operating distance up to 5000m line of sight.
- LED indication for power, battery state, run & radio transmission.
- Low voltage DC supply.
- Low power consumption.
- Internal battery backup.
- IP65 enclosure.
- Whip antenna's fitted as standard.
- 9 way D Type RS232 for serial connection.
- Cable gland for external power connection.
- Plug in connectors for ease of wiring
- Small size for simple installation.
- Uses the latest RF Technology for system security.
- No programming required.
- Low power radio that is licence free.
- **For use in non hazardous areas & non safety critical applications.**

Specification:

- Input/output – RS232 - 9 way D Type.
- Range – up to 5000m line of sight.
- Power supply – 12 to 24VDC.
- Maximum power consumption – 400mA @12VDC.
- RF power output – 26dBm @ 869.50MHz.
- Internal battery – rechargeable giving up to 20 minutes backup.
- Enclosure – ABS, 125x85x55mm, IP65 rating.
- Antenna – ¼ wave whip with SMA male fitting.
- Weight - 325g approx.
- Operating temperature - 0 to 50 degrees C.
- Cable gland power connection.

Certification:

- EN 301 489-3.
- EN 300 220-3.
- EN 300 489.
- EN 60950.
- CEPT 70-03 Recommendation.
- R&TTE compliance (1999/5/EC Directive).
- Low Voltage Directive (LVD) 2006/95/EC.



Datacom Technology Ltd

45 Trent View Gardens, Radcliffe on Trent, Nottingham, NG12 1AY.

Tel: 0115 847 8756 Fax: 0115 933 3868

www.datacomtechnology.co.uk

Email: info@4datacom.co.uk